
Components for BZC Control Stations HA Flameproof push button



■ Catalogue number logic

HA (A for short)



- Explosion protection to
 - -CENELEC
 - -IEC
 - -NEC
- Can be used in

Zone 1 and Zone 2

Zone 21 and Zone 22

Class I, Zone 1 and Zone 2

Class I, Division 1, Groups A, B, C, D

- ♦ Five different ways of operation
 - -Spring-return push button
 - -Key-operated push button
 - -Mushroom stay-put emergency push button
 - -Mushroom turn-to-release emergency push button
 - -Rotary push button
- Mushroom stay-put emergency push button mushroom turn-to-release emergency push button can be equipped with protection cover, please specify when ordering. Material of protection cover: stainless steel and PC, please specify when ordering.



Technical data

HA Flameproof push button

Explosion protection

Global (IECEx)

Gas and dust

Europe (ATEX)

Gas and dust

Certificates

Conformity to standards

Rated voltage

Rated current

Degree of protection Ambient temperature IECEx CML 17.0161U

Ex db IIC Gb

Ex tb IIIC Db

CML 17 ATEX 1289U

II 2 G Ex db IIC Gb

IECEx; ATEX

EN 60079-0, EN 60079-1, EN 60079-31

IEC 60079-0, IEC 60079-1, IEC 60079-31

660V AC; 440V DC

10A (for 660V AC); 6A (for 440V DC)

IP66

-60℃~+70℃

Zones 1&2; 21&22

Components for BZC Control Stations HA Flameproof push button

Selection table					
Cover mounting	Specification	n	Code	Ordering code	Weight (kg)
		Red	а	40036A	0.15
		Green	b	40036B	0.15
	Spring-return push button	Yellow	С	40036C	0.15
		Black	d	40036D	0.15
		Blue	е	40036E	0.15
		O White	р	40036F	0.15
	Mushroom stay-put emergency push button	Red	f	40037	0.27
	Mushroom turn-to-release emergency push button	Red	g	40040	0.27
	Key-operated mushroom emergency push button	Red	h	40040A	0.30
	Rotary push button	Black	i	40039	0.27
	Key-operated push button	Black	j	40038	0.27
	Push button with indicator	Red	k	40057A	0.15
		Green	1	40057B	0.15
		Yellow	m	40057C	0.15
		Blue	n	40057D	0.15
		O White	0	40057E	0.15




General Catalogue 01.04.2023 http://www.waromgroup.com 4/11

Components for BZC Control Stations HA Flameproof push button


Selection table of push button contact						
Version	Specification	Contact code	Ordering code	Weight (kg)		
C TO CO	1 1NC	T1	40023	0.03		
Screw type	1NO	S1	40024	0.03		

Accessories							
Description	Material	Ordering code	Weight (kg)				
Emergency push button protection cover	PC	40196	0.03				
Emergency push button protection cover	Stainless steel	40197	0.15				
Emergency push button warning plate	LF2	40198	0.003				






Dimension drawings (all dimensions in mm) - subject to alteration




Flameproof Thread

Rotary push button




Flameproof Thread

Key-operated push button




Flameproof Thread


Mushroom stay-put/ turn-to-release emergency push button




Flameproof Thread

Key-operated mushroom emergency push button





HA Emergency push button with stainless steel protection cover



HA Emergency push button with PC protection cover



General Catalogue 01.04.2023 http://www.waromgroup.com 4/13